

SAFETY DATA SHEET ACCORDING TO EC-REGULATIONS 1907/2006 (REACH) & 1272/2008 (CLP)

IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

GHS Product IdentifierCERECLOR™ S40/S45/S50 /S52/S52HV/
S52SS/51L/S54/S55/S56/S58/S60/S63

EC INDEX No. 602-095-00-X

Alternative names Medium-chain chlorinated paraffins/alkanes, C14-C17, chloro

Alkanes, C14-17, chloro

C14-17 chlorinated paraffin (chlorination: 40 - 60%)

REACH Registration No. 01-2119519269-33-XXXX

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s) lubricants and lubricant additives , anti-set off and adhesive agent , flame

retardant , plasticiser in polyvinyl chloride and in paints, extreme pressure additives (metal cutting/working fluids) , solvent in carbonless copy paper and fat

liquors used in leather processing, softeners

For details on specific grades please refer to technical literature.

Uses advised againstAs a plasticiser in products for childrens' toys and food contact applications.

1.3 Details of the supplier of the safety data sheet

Company Identification INEOS Chlor Limited

Runcorn Site HQ South Parade, PO Box 9 Runcorn, Cheshire, WA7 4JE

Tel: (01928) 561111, Fax: (01928) 516636

E-Mail (competent person) msds.chlor@ineos.com

1.4 Emergency telephone number

IN AN EMERGENCY DIAL 999 (UK only) or 112 (EU)

For specialist advice in an emergency telephone Runcorn +44 (0)1928 572000

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Directive 67/548/EEC & Directive 1999/45/EC N : Dangerous for the environment.

R50/53 Very toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment. R64 May cause harm to breastfed babies.

R66 Repeated exposure may cause skin dryness and cracking.

Regulation (EC) No. 1272/2008 (CLP) Aquatic Acute 1, Aquatic Chronic 1, Lact.

2.2 Label elements

Hazard Statements H362: May cause harm to breast-fed children.

H410: Very toxic to aquatic life with long lasting effects.

Signal word(s) WARNING

Hazard pictogram(s)



Precautionary statement(s)

P273: Avoid release to the environment.

P391: Collect spillage.

P501: Dispose of contents/container to: An approved hazardous waste facility.

P260: Do not breathe mist/vapours/spray.

P263: Avoid contact during pregnancy/while nursing.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Additional label requirements

EUH066: Repeated exposure may cause skin dryness or cracking.

Revision: GHS01 Revision: Date: 11/2010 Page: 1 / 7



2.3 Other hazards

This product does not contain any of the PBT substance, short-chain chlorinated paraffins (CAS No 85535-84-8).

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Hazardous ingredient(s)	%(w/w)	CAS No.	EC No.	H - Codes
C14-17 Chlorinated paraffin	100	085535-85-9	287-477-0	H362, H410
				EUH066

4. FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation Remove patient from exposure, keep warm and at rest.

Skin Contact Remove contaminated clothing. Wash skin with soap and water.

Eye Contact Irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 10 minutes.

Obtain medical attention.

Ingestion Do not induce vomiting. Wash out mouth with water and give 200-300 ml (half a pint) of water

to drink

4.2 Most important symptoms and effects, both acute and delayed

If skin irritation or rash occurs: Get medical advice/attention.

4.3 Indication of the immediate medical attention and special treatment needed

Unlikely to be required but if necessary treat symptomatically.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing Media Normal extinguishing media. Water spray, dry powder or carbon dioxide.

Unsuitable Extinguishing Media None anticipated.

5.2 Special hazards arising from the substance or mixture

Non-flammable. May decompose if heated above 200 Deg C with liberation of hydrogen chloride.

5.3 Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear suitable gloves and eye/face protection.

6.2 Environmental precautions

Do not allow to enter drains, sewers or watercourses.

6.3 Methods and material for containment and cleaning up

Caution - spillages may be slippery. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal or recovery.

6.4 Reference to other sections

See Section: 8, 13

6.5 Additional information

Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

Revision: GHS01 Revision: Date: 11/2010 Page: 2 / 7



7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Provide adequate ventilation where operational procedures demand it. Do not allow to enter drains, sewers or watercourses.

7.2 Conditions for safe storage, including any incompatibilities

Keep container dry. Keep away from direct sunlight.

Keep only in the original container at a temperature not exceeding (°C): 40

Storage vessels should be made of lined mild steel in accordance with the advice given in CERECLOR™ Bulk Storage and Handling brochure. Total storage life at recommended conditions: 2 years if stored in accordance with advice given above.

7.3 Specific end use(s)

None

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters

No Occupational Exposure Limit Assigned

DNEL	oral	Inhalation	Dermal
Industry - Long Term - Local effects	-	-	-
Industry - Long Term - Systemic effects	-	1.6 mg/m³	47.9 mg/kg bw/day
Industry - Short term - Local effects	-	-	-
Industry - Short term - Systemic effects	-	-	
Consumer Long Term - Local effects	-	-	-
Consumer Long Term - Systemic effects	0.58 mg/kg bw/day	2.0 mg/m ³	28.75 mg/kg bw/day
Consumer Short term - Local effects	-	-	-
Consumer Short term - Systemic effects	-	-	

Environment	PNEC
Aquatic Compartment (including sediment)	1 μg/l Fresh water
	0.2 µg/l Marine water
	80 mg/l Micro-organisms (sewage treatment plant)
	5 mg/kg Wet Sediment (Fresh water)
	1 mg/kg Wet Sediment (Marine water)
Terrestrial Compartment	10.5 mg/kg Wet (Soil)
Atmospheric Compartment	No data.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation where operational procedures demand it. Use appropriate containment to avoid environmental contamination.

Personal Protection

Eye/face protection If splashing or mist is likely to occur: Wear eye/face protection.

Skin protection Good working practice suggests gloves and goggles should be worn. The following materials

are suitable for protective gloves (permeation time >= 8 hours): Nitrile rubber.

Check with protective equipment manufacturer's data.

Respiratory protection Wear suitable respiratory protective equipment if exposure to mist is likely. Where a

cartridge/canister respirator is suitable use: Type P (EN143) Check with protective equipment manufacturer's data.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Form Liquid Odour Slight.

Boiling Point (Deg C) >200, Decomposes below boiling point.

Flash Point (Deg C) None.

Vapour Pressure (mm Hg)practically non-volatileDensity (g/ml)1.10 - 1.45 at 25 Deg C

Solubility (Water) insoluble

Solubility (Other) Soluble in most aromatic hydrocarbons, chlorinated solvents, esters and ketones.

Pour Point (Deg C) -40 to +27

Revision: GHS01 Revision: Date: 11/2010 Page: 3 / 7



9.2 Other information

None

10. STABILITY AND REACTIVITY

10.1 Reactivity

Non-reactive

10.2 Chemical Stability

Stable at ambient temperatures.

10.3 Possibility of hazardous reactions

Can react with alkali metals and alkaline earth metals which have a strong affinity for chlorine. Can react with iron, zinc and aluminium at high temperatures leading to decomposition.

10.4 Conditions to avoid

strong oxidising agents, heat and hot surfaces.

Chlorinated paraffins tend to soften or swell most rubbers.

10.5 Incompatible materials

Keep away from strong oxidising agents.

10.6 Hazardous Decomposition Product(s)

Prolonged heating at temperatures in excess of 70 Deg C or heating above 200 Deg C for short periods of time will result in decomposition and liberation of hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Low oral toxicity. Unlikely to be hazardous by inhalation.

Repeated exposure may cause skin dryness or cracking. Anticipated to have low dermal toxicity

This health hazard assessment is based on information available on similar products.

Test result / data

Acute oral toxicity

The acute oral LD50 for C14-17 chlorinated paraffins in rats is >2 g/kg bw.

Acute inhalation toxicity No data available for C14-C17 chlorinated paraffins.

No deaths were seen in acute inhalation studies in rats exposed to air containing a C12 chlorinated paraffin (59% chlorination) at 3.3 mg/l or a 50% chlorinated short chain chlorinated paraffin (unspecified chain length) at 48 mg/l for 1 hr.

Acute dermal toxicity

No data available for C14-C17 chlorinated paraffins.

The acute dermal LD50 of a C10-13 chlorinated paraffin (52% chlorinated) in rats

and a C12 chlorinated paraffin (59% chlorinated) in rabbits is >2g/kg bw.

Skin irritation. Slight skin irritation reported in two studies conducted according to OECD Guideline

404 using undilute C14-17 chlorinated paraffins (40 & 52% chlorination - containing

1% epoxy stabiliser).

Serious eye damage/irritation Slight eye irritation reported in two studies conducted according to OECD Guideline

405 using undilute C14-17 chlorinated paraffins (40 & 52% chlorination - containing

1% epoxy stabiliser).

Respiratory irritation No reliable data available. There are no reports relating to this endpoint despite the

widspread use of this substance.

Sensitisation It is not a skin sensitiser in animal tests.

Repeated dose toxicity Repeated exposure to high levels may produce liver and kidney damage.


Chronic ingestion studies in animals have shown that repeated doses of a representitive chlorinated paraffin (C14-17, 52%) gave no adverse effects at doses 23 mg/kg/day (90 day study). Slight effects on the liver were seen at doses >360 mg/kg/day. These effects occur after the administration of high oral doses of C14-C17 chlorinated paraffins to the female rat, a situation that would not arise under

any reasonably forseeable circumstances of human exposure.

Germ cell mutagenicity

Not mutagenic to bacteria or in in-vivo mouse bone marrow micronucleus assays.

Revision: GHS01 Revision: Date: 11/2010 Page: 4 / 7





Carcinogenicity MCCPs have not been tested for carcinogenicity.

Chlorinated paraffins, as a group of chemicals are not genotoxic.

Their lack of genotoxic activity together with the results of other studies leads us to conclude that chlorinated paraffins are unlikely to present a carcinogenic hazard to

man under normal conditions of handling and use.

Reproductive toxicity No reported effects on fertility at doses up to 400 mg/kg/day.

No effects in conventional development toxicity studies with doses up to 5000

mg/kg/day (rat) and 100 mg/kg/day (rabbit).

Mortality due to internal haemorrhaging has been seen in newborn rats, reared by

dams fed on high doses of a similar chlorinated paraffin.

Specific target organ toxicity - single

exposure (STOT SE)

Not classified

Specific target organ toxicity — repeated exposure (STOT RE)

Not classified

Aspiration hazard Not an aspiration hazard

12. ECOLOGICAL INFORMATION

12.1 Toxicity

A representative C14-17 chlorinated paraffin has been shown to be toxic to daphnia in laboratory studies. It showed a low level of toxicity to another aquatic invertebrate species (gammarus) and to fish and algae.

Toxicity to aquatic species:

Aquatic invertebrates: Daphnia magna 48hr - EC50 = 0.006 mg/l

Crustacean(Gammarus pulex) 96 hr - LC50 = >1.0 mg/l Fish : Alburnus alburnus (bleak) 96hr - EC50 = >3.2 mg/l

Algae (Selenastrum capricornutum) 96 hr - EC50 (biomas) = >3.2 mg/l

M-Factor = 100

12.2 Persistence and degradability

Concentrations in the atmosphere are likely to be very small due to low volatility. Estimated atmospheric half life is 1 - 2 days. Biodegredation in soil: Studies conducted on C14.5 & C15.4 (average C chain length) with 43.5% & 50% chlorination showed 57% and 51% degradation of the test substance after 36 hours.

Biodegradation in water and sediments: Simulation tests conducted on two C16 chlorinated paraffins (containing 35% Cl2 & 58% Cl2) gave a half-life (DT50) of 12 days and 58 days in freshwater sediment respectively.

12.3 Bioaccumulative potential

The product has potential for limited bioaccumulation. (BCF <2000 L/kg, BMF <1)

12.4 Mobility in soil

The product is predicted to have low mobility in soil.

12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

This product does not contain any of the PBT substance, short-chain chlorinated paraffins (CAS No 85535-84-8).

12.6 Other adverse effects

None known

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

This material and/or its container must be disposed of as hazardous waste.

Do not discharge into drains or the environment, dispose to an authorised waste collection point.

13.2 Additional information

Disposal should be in accordance with local, state or national legislation.

Revision: GHS01 Revision: Date: 11/2010 Page: 5 / 7



14. TRANSPORT INFORMATION

14.1 Road/Rail

UN No. 308

Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S

(CHLORINATED PARAFFINS (C14-17))

ADR/RID Class 9
Packing Group III
Label. 9

Environmental hazards Dangerous for the environment.

Tunnel Restriction Code (E)

14.2 SEA (IMDG)

UN No. 3082

Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S

(CHLORINATED PARAFFINS (C14-17))

IMDG Class 9
Packing Group III
Label. 9

Marine Pollutant Classified as a Marine Pollutant (P)

14.3 Air (ICAO/IATA)

UN No. 3082

Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S

(CHLORINATED PARAFFINS (C14-17))

ICAO-TI Class 9
Packing Group III
Label. 9

14.4 Additional Information

None

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Control of Substances Hazardous to Health Regulations (COSHH) 2002 SI 2002/2677 and COSHH Essentials: Easy steps to control chemicals - Control of Substances Hazardous to Health Regulations HSG193.

Inventory Status

Listed in: Australia (AICS) Canada (DSL/NDSL) China (IECSC) European Union (EINECS/ELINCS) South Korea (KECI) Philippines (PICCS) New Zealand Inventory (NZIoC)

15.2 Chemical Safety Assessment

A Chemical Safety Assessment (CSA) has been completed for this substance.

16. OTHER INFORMATION

Indication of changes

All sections revised according to CLP/GHS requirements.

LEGEND

WEL: Workplace Exposure Limit (UK HSE EH40)

COM: The company aims to control exposure in its workplace to this limit TLV: The company aims to control exposure in its workplace to the ACGIH limit TLV-C: The company aims to control exposure in its workplace to the ACGIH Ceiling limit MAK: The company aims to control exposure in its workplace to the German limit

Sk : Can be absorbed through skin

Sen : Capable of causing respiratory sensitisation

Bmgv: Biological monitoring guidance value (UK HSE EH40)

ILV : Indicative Limit Value (UK HSE EH40)
IOELV : Indicative Occupational Exposure Limit Value

Key literature references

Chemical Safety Report, Medium-chain chlorinated paraffins/alkanes, C14-C17, chloro (13/9/2010) GESTIS -database on hazardous substances

Revision: GHS01 Revision: Date: 11/2010 Page: 6 / 7



Further information

CERECLOR™ is a trade mark, the property of INEOS Chlor Limited.

INEOS™ is a trade mark, the property of INEOS Capital Limited.

Information in this publication is believed to be accurate and is given in good faith, but it is for the Customer to satisfy itself of the suitability for its own particular purpose. Accordingly, INEOS Chlor Limited gives no warranty as to the fitness of the Product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that such exclusion is prevented by law. Freedom under Patent, Copyright and Designs cannot be assumed.

Revision: GHS01 Revision: Date: 11/2010 Page: 7 / 7